

Model ES SERIES

ELECTRIC SCISSOR LIFTS



Features

Proportional Controls
Industry Leading Duty Cycles
Drywall Gate¹
Battery Condition Indicator
110V-AC Receptacle in Platform
Fold-Down Guard Rails²
Automatic Traction Control (ATC)
20 Amp Automatic SCR Charger
Slide-Out Battery Trays
All Motion Alarm
Horn
Hourmeter
Manual Descent Pull Cable
36 in. (91 cm) Roll-Out Deck Extension³
50 in. (1.27 m) Roll-Out Deck Extension⁴
Moveable, Removable Platform Control Console with Rail Mounting Bracket
Lanyard Attach Points
Lubrication Free Scissor Arm Bushings
Scissor Maintenance Prop
Mechanized Pothole Protection
Powder-Coated
Nickel Plated Pins
Machine Tie Downs
Fork Lift Pockets, Lift from Side and Rear
Four 6V, 220 Amp-Hour Deep Cycle Batteries
Tilt Alarm and Light
On-Board Diagnostics/Battery State-of-Charge LEDs

1. Not included on 1930ES.

2. Optional on 1930ES.

3. 1930ES, 2030ES, and 2630ES.

4. 2646ES and 3246ES.

Accessories & Options

Spring-Loaded Gate
Flashing Amber Beacon
245 Amp-Hour Batteries¹
1,000W-AC Inverter
Lifting Lugs
UL® EE Rating²
Platform Padding
Platform Padding with Proximity Switches
Quik Welder Prep Package
1/2 in. Airline
Nite Bright
220 Amp-Hour AGM Batteries
Special Hydraulic Oils
Accessory Packages:
Electrician's Package
Plumber's Package
Plant Maintenance Package
Panel Carrier Accessory¹
Pipe Rack Accessory¹
Quick Welder® Package
JLG® Workstation

1. Not available on the 1930ES.

2. Not available with AGM Batteries.

3. Not available with 1930ES, 2030ES, 2630ES.



Cleaner Operation, Longer Runtime

- Only two hoses and four fittings mean improved reliability and reduced service requirements
- Double the duty cycles thanks to super-efficient electric drive
- Quieter operation for sound-sensitive areas and applications

Higher Capacities and Larger Platforms

- Holds up to 1,000 lb on the large 44 in. x 98.5 in. platform
- Up to 250 lb capacity on the extension platform
- Narrow models drive through doorways and tight aisles
- Wide models provide more workspace with wider decks and longer platform extensions



Mobility and Versatility

- Front-wheel drive and front-wheel steering offer tight turning circles
- Durable, non-skid aluminum deck
- Optional Workstation in the Sky® accessory packages enhance productivity

Model ES SERIES

ELECTRIC SCISSOR LIFTS

Specifications



Dimensions

Platform Height—Elevated

1930ES	18 ft 9 in. (5.72 m)
2030ES	20 ft (6.10 m)
2630ES	25 ft 6 in. (7.77 m)
2646ES	26 ft (7.92 m)
3246ES	31 ft 9 in. (9.68 m)

A. Platform Height—Lowered

1930ES	35 in. (0.89 m)
2030ES	43.5 in. (1.10 m)
2630ES	48.5 in. (1.23 m)
2646ES	49.5 in. (1.26 m)
3246ES	49.5 in. (1.26 m)

B. Platform Railing Height

43.3 in. (1.10 m)

C. Overall Height—Rails Lowered

1930ES	N/A
2030ES	5 ft 11.5 in. (1.80 m)
2630ES	6 ft 4.5 in. (1.94 m)
2646ES/3246ES	6 ft 5.5 in. (1.97 m)

D. Platform Size

1930ES	30 x 73.5 in. (0.76 x 1.87 m)
2030ES/2630ES	30 x 90.5 in. (0.76 x 2.3 m)
2646ES/3246ES	44 x 98.5 in. (1.12 x 2.5 m)

E. Platform Extension

1930ES/2030ES/2630ES	35.5 in. (0.9 m)
2646ES/3246ES	50 in. (1.27 m)

F. Overall Width

1930ES/2030ES/2630ES	30 in. (76 cm)
2646ES/3246ES	46 in. (1.17 m)

G. Overall Length

1930ES	6 ft 1.5 in. (1.87 m)
2030ES/2630ES	7 ft 6.5 in. (2.3 m)
2646ES/3246ES	8 ft 2.5 in. (2.5 m)

H. Wheelbase

1930ES	5 ft 3 in. (1.6 m)
2030ES/2630ES	6 ft 2 in. (1.88 m)
2646ES/3246ES	6 ft 10 in. (2.09 m)

I. Ground Clearance

1930ES/2030ES/2630ES	3.5 in. (8.8 cm)
2646ES/3246ES	5 in. (12.7 cm)

Platform Capacity

1930ES	500 lb (227 kg)
2030ES	800 lb (363 kg)
2630ES	500/800 lb (227/363 kg)
2646ES	1,000 lb (454 kg)
3246ES	700/1,000 lb (318/454 kg)

Capacity on Platform Extension

250 lb (113 kg)

Lift/Lower Time

1930ES	26/30 seconds
2030ES	28/40 seconds
2630ES	33/37 seconds
2646ES	41/50 seconds
3246ES	55/62 seconds

Maximum Drive Height

Fully Elevated

Weight*

1930ES	2,685 lb (1,218 kg)
2030ES	3,830 lb (1,737 kg)
2630ES	4,815 lb (2,184 kg)
2646ES/ 3246ES	4,945 lb (2,243 kg)

Ground Bearing Pressure

1930ES	109 psi (7.66 kg/cm ²)
2030ES	81 psi (5.69 kg/cm ²)
2630ES	90 psi (6.32 kg/cm ²)
2646ES/ 3246ES	87 psi (6.11 kg/cm ²)

Chassis

Drive Speed—Elevated

0.5 mph (0.8 km/h)

Drive Speed—Lowered

1930ES	3.0 mph (4.82 km/h)
2030ES/2630ES	2.75 mph (4.43 km/h)
2646ES/3246ES	2.50 mph (4.00 km/h)

Gradeability

25%

Turning Radius (Inside)

Zero

Turning Radius (Outside)

1930ES	69 in. (1.75 m)
2030ES/2630ES	81 in. (2.06 m)
2646ES/3246ES	95.1 in. (2.41 m)

Tire Size/Type

1930ES	12.5 x 4 in. Non-Marking Solid
2030ES/2630ES/2646ES/3246ES	16 x 5 in. Non-Marking Solid
Brakes	Electric, Friction

Power Source

Batteries	4 x 6V, 220 amp-hr
Charger	20 Amp Automatic
Pump	Fixed Displacement Gear
Hydraulic Reservoir	
1930ES/2030ES/2630ES	1.25 gal. (4.73 L)
2646ES/3246ES	1.7 gal. (6.4 L)
Drive	24V Electric (8 hp)

*Certain options or country standards will increase weight.



The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.6-2006, and CSA Standard CAN3-B354.2-M82, as originally manufactured for intended applications.



JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company

Form No.: SS-ES-908
Part No.: 3131580
R051103
Printed in USA